

## Eurohook specification sheet

**Heavy duty one piece moulded U.V Stabilised Polypropylene bag and hat hook. Suitable for indoor and or outdoor usage. Two point screw fixing allows for installation to a wide variety of substrates.**

Available in a range of colours Euro Bag and Hat hooks are rated to support up to 40kg, and provide for two hanging points. Hooks are designed with safety in mind. A large top--hanging bell is moulded with rounded corners suitable for supporting wide strap items such as backpacks etc. A smaller support hook is great for library bags, hats and or smaller, lighter items. Manufactured in Australia by Linc Furntiure Pty Ltd.

### SPECIFICATIONS

#### MATERIALS:

Moulded Co--polymer Polypropylene UV Stabilised and fully compounded at the time of manufacture.

#### AVAILABLE COLOURS:

Tango (1655C), Red (7627C), Yellow (113C), Green (7726C), Blue (2175C), Black (Pantone Colour Codes)

#### PERFORMANCE:

Top (Large Bell), up to 40kgs static load with-out deformation and or breakage. Lower Hook (Small Hook), up to 5kgs static load without deformation and or breakage.

#### FIXING POINTS:

Two (2) screw/rivet fixing points – we suggest for normal use 2 x 10 gauge x 20mm pan head self tapping screw fasteners be used to fix a Euro hook to an 18mm thick substrate.

#### WARRANTY:

5 year structural warranty, covering failure associated with faulty materials and workmanship. Whilst

UV Stabilised materials are used to manufacture these items, it is understood that there will be some discoloration associated with UV degradation over time. Safehook uses the blue wool scale to determine a suitable warrantable level of degradation. Safehook does not warranty its products for failures associated with abuse and or misuse. A regular inspection of goods is recommended to ensure goods remain fit for purpose. Where appropriate damaged product should be removed from service ASAP and referred to Safehook for assessment.

#### INSTALLATION:

Safehook recommends that hooks be mechanically fastened to a secure, stable substrate capable of holding the combined weight of the number of hooks to be installed x 40kg per hook @300mm centres. Eurohooks should be fastened to a surface that has a face measurement of at least 85mm wide. Care should be taken not to damage the hook moulding during installation. Safehook takes no responsibility for the installation of hooks where hooks are installed by any party other than Linc Furniture or its approved installers. Refer Safehook Australia's warranty for further details. Suitability of substrates to mount hooks to should be referenced to the supplier of manufacturer of that substrate. Safehook takes no responsibility for the suitability of such substrate.

Note hooks have not been designed to be used as climbing devices and or to support the weight of items or exceeding 40kgs and should not be used for this purpose.

